

View Online at <https://aerobasegroup.com/nsn/4330-01-386-4229>

**Mounting Type:**

Threaded hole head

**Body Outside Diameter:**

3.000 inches

**Body Height:**

11.420 inches

**Filtration Rating In Microns:**

10.0

**Drop Pressure:**

5.0 pounds per square inch

**Differential Pressure:**

10000.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

0.750 inches

**End Application:**

Usns stalwart class

**Mounting Facility Thread Direction:**

Right-hand

**Design Type:**

Reusable

**Temperature Rating:**

225.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Filtering Media Design:**

Porous single filtering media response

**First Intake Connection Type:**

Threaded internal tube head side

**Mounting Facility Thread Size:**

0.250 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.062 inches

**First Intake Thready Qty Per Inch (tpi):**

12

**First Intake Thread Class:**

3b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Extended length disposable element; color coded warning indicator; 40.0 psi cracking pressure on bypass valve; hex shape body

**Material:**

Rubber buna n seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000