## NSN 4330-01-386-9884

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-386-9884

Mounting Type:
Threaded hole head
Mounting Hole Quantity:
4
Body Outside Diameter:
3.580 inches
Body Height:
7.360 inches
Filtration Rating In Microns:
20.0 absolute
Drop Pressure:
12.0 pounds per square inch
Differential Pressure:
2250.0 pounds per square inch
Distance Between Mounting Hole Centers:
Between 1.181 inches and 1.772 inches
End Application:
Nimitz class cvn
Mounting Facility Thread Direction:
Right-hand
Design Type:
Reusable
Tempurature Rating:
Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit
Features Provided:
Differential pressure indicator
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unf
Maximum Operating Pressure:
1500.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response or porous single filtering media response
First Intake Connection Type:
Threaded internal tube head side
Mounting Facility Thread Size:
0.250 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection

Un

First Intake Thread Series Designator:

## **NSN 4330-01-386-9884** Fluid Filter - Page 2 of 2



First Intake Thread Size:
1.062 inches
First Intake Thready Qty Per Inch (tpi):
12
First Intake Thread Class:
2b
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Pop-up type indicator; no by-pass
Material:
Rubber buna n seal
Media For Which Designed:
Fuel/oil, hydrocarbon and water/alcohol mixture
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A24000