NSN 4330-01-389-6409

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-389-6409

Mounting Type:
Unthreaded hole head
Mounting Hole Diameter:
0.270 inches
Mounting Hole Quantity:
2
Body Outside Diameter:
4.090 inches
Body Height:
12.640 inches
Filtration Rating In Microns:
1.0 absolute
Drop Pressure:
20.0 pounds per square inch
Differential Pressure:
7500.0 pounds per square inch
Distance Between Mounting Hole Centers:
3.120 inches
Design Type:
Reusable
Tempurature Rating:
Between -20.0 degrees fahrenheit and 275.0 degrees fahrenheit
Features Provided:
By-pass valve and differential pressure indicator
Filtering Element Quantity:
1
Maximum Operating Pressure:
3000.0 pounds per square inch
Filtering Media Design:
Porous single filtering media response
First Intake Connection Type:
Threaded internal tube head side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Unf
First Intake Thread Size:
0.750 inches
First Intake Thread Class:
3b
First Intake Thread Direction:

Right-hand

NSN 4330-01-389-6409

Fluid Filter - Page 2 of 2

Fiig: A24000



Filtering System For Which Designed:
Full flow
Special Features:
2.500 in. Min. Clearance required for bowl and element removal; electrical differential indicator w/automatic reset; 50.0 psi bypass setting
Material:
Plastic seal
Media For Which Designed:
Fuel/oil, hydrocarbon or ethylene
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No