

View Online at <https://aerobasegroup.com/nsn/4330-01-389-6409>

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

0.270 inches

Mounting Hole Quantity:

2

Body Outside Diameter:

4.090 inches

Body Height:

12.640 inches

Filtration Rating In Microns:

1.0 absolute

Drop Pressure:

20.0 pounds per square inch

Differential Pressure:

7500.0 pounds per square inch

Distance Between Mounting Hole Centers:

3.120 inches

Design Type:

Reusable

Temperature Rating:

Between -20.0 degrees fahrenheit and 275.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Porous single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Unf

First Intake Thread Size:

0.750 inches

First Intake Thread Class:

3b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

2.500 in. Min. Clearance required for bowl and element removal; electrical differential indicator w/automatic reset; 50.0 psi bypass setting

Material:

Plastic seal

Media For Which Designed:

Fuel/oil, hydrocarbon or ethylene

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000