## NSN 4330-01-390-3593

Fluid Filter Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-390-3593

View Online at https://aerobasegroup.com/nsn/4330-01-390-3593
Mounting Type:
Unthreaded hole base
Mounting Hole Diameter:
0.8125 inches
Mounting Hole Quantity:
8
Filtration Rating In Microns:
10.0
Drop Pressure:
5.0 pounds per square inch
Differential Pressure:
30.0 pounds per square inch
Distance Between Mounting Hole Centers:
27.500 inches
End Application:
W/s code fb, spruance class dd
Design Type:
Reusable
Tempurature Rating:
Between 100.0 degrees fahrenheit and 110.0 degrees fahrenheit
Unit Quantity:
2
Features Provided:
Drain cock and flow control valve
Filtering Element Quantity:
22
Maximum Operating Pressure:
120.0 pounds per square inch
First Intake Connection Type:
Plain face flange line
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
Filtering System For Which Designed:
Full flow
Special Features:
Temperature 40deg f to 85deg f for jp-5
Material:
Steel comp 304 body
Media For Which Designed:
Fuel/oil, hydrocarbon
Shelf Life:

N/a

## NSN 4330-01-390-3593

Fluid Filter Assembly - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A24000