# NSN 4330-01-390-5985

Fluid Filter - Page 1 of 2



#### Mounting Type:

Threaded hole top

# Mounting Hole Quantity:

4

# Body Outside Diameter:

5.200 inches

#### **Body Height:**

26.220 inches

#### **Filtration Rating In Microns:**

3.0

#### Drop Pressure:

6000.0 pounds per square inch

#### **Differential Pressure:**

12000.0 pounds per square inch

#### **Distance Between Mounting Hole Centers:**

### Between 3.875 inches and 5.250 inches

Design Type:

#### Limited

Filtering Element Quantity:

1

### Mounting Facility Thread Series Designator:

Uns

#### First Intake Connection Type:

Unthreaded internal tube top

#### Mounting Facility Thread Size:

0.500 inches

#### First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

#### First Intake Inside Diameter:

1.500 inches

#### Filtering System For Which Designed:

By-pass flow

Material:

Steel body

#### Media For Which Designed:

Fuel/oil, hydrocarbon

#### Surface Treatment:

Oxide body

#### Style Designator:

Body and cover assembly (bolted flange)

# Shelf Life:

N/a



# NSN 4330-01-390-5985

Fluid Filter - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A24000

