NSN 4330-01-390-7510

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-390-7510

Mounting Type:
Unthreaded hole head
Mounting Hole Diameter:
0.271 inches
Mounting Hole Quantity:
2
Body Length:
4.108 inches
Body Width:
2.924 inches
Body Height:
7.080 inches
Filtration Rating In Microns:
6.0 absolute and 0.45
Drop Pressure:
13.5 pounds per square inch
Differential Pressure:
3000.0 pounds per square inch
Distance Between Mounting Hole Centers:
3.130 inches
End Application:
W/s code 36, missile, air launch
Design Type:
Reusable
Tempurature Rating:
-20.0 degrees fahrenheit and 275.0 degrees fahrenheit
Features Provided:
Differential pressure indicator
Filtering Element Quantity:
1
Maximum Operating Pressure:
5000.0 pounds per square inch
First Intake Connection Type:
Threaded internal tube head side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
Distance From Bottom Of Body To Center Of Inlet:
5.750 inches
First Intake Thread Series Designator:
Unf
First Intake Thread Size:

0.750 inches

NSN 4330-01-390-7510

Fluid Filter - Page 2 of 2



First Intake Thread Class:
2b
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Material:
Rubber synthetic seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Tee type (hydraulic)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000