

View Online at <https://aerobasegroup.com/nsn/4330-01-391-0749>

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

0.270 inches

Mounting Hole Quantity:

2

Body Length:

4.090 inches

Body Width:

2.900 inches

Body Height:

8.760 inches

Filtration Rating In Microns:

3.0

Differential Pressure:

150.0 pounds per square inch

Distance Between Mounting Hole Centers:

3.120 inches

End Application:

W/s code ac, support equipment, b

Design Type:

Reusable

Temperature Rating:

-20.0 degrees fahrenheit and 275.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

5.760 inches

First Intake Thread Series Designator:

Unf

First Intake Thread Size:

0.750 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Electrical switch (sptd) with 3-pin receptacle, auto reset; visual indicator without thermal lockout

Material:

Plastic polytetrafluoroethylene seal

Media For Which Designed:

Fuel/oil, hydrocarbon and water/alcohol mixture

Style Designator:

Tee type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000