

View Online at <https://aerobasegroup.com/nsn/4330-01-391-0749>

**Mounting Type:**

Unthreaded hole head

**Mounting Hole Diameter:**

0.270 inches

**Mounting Hole Quantity:**

2

**Body Length:**

4.090 inches

**Body Width:**

2.900 inches

**Body Height:**

8.760 inches

**Filtration Rating In Microns:**

3.0

**Differential Pressure:**

150.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

3.120 inches

**End Application:**

W/s code ac, support equipment, b

**Design Type:**

Reusable

**Temperature Rating:**

-20.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal tube head side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**Distance From Bottom Of Body To Center Of Inlet:**

5.760 inches

**First Intake Thread Series Designator:**

Unf

**First Intake Thread Size:**

0.750 inches

**First Intake Thread Class:**

2b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Electrical switch (sptd) with 3-pin receptacle, auto reset; visual indicator without thermal lockout

**Material:**

Plastic polytetrafluoroethylene seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water/alcohol mixture

**Style Designator:**

Tee type (hydraulic)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000