NSN 4330-01-391-8316

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-391-8316

Mounting Type:
Threaded hole top
Mounting Hole Quantity:
6
Body Outside Diameter:
6.100 inches
Body Height:
19.800 inches
Filtration Rating In Microns:
3.0 absolute and 0.5
Differential Pressure:
290.0 pounds per square inch
Distance Between Mounting Hole Centers:
2.200 inches and 1.970 inches
End Application:
W/s code ac support equipment
Mounting Facility Thread Direction:
Right-hand
Design Type:
Reusable
Features Provided:
Differential pressure indicator
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unc
Filtering Media Design:
Layered single filtering media response
First Intake Connection Type:
Threaded internal tube head side
Mounting Facility Thread Size:
0.375 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Unf
First Intake Thread Size:
1.625 inches
First Intake Thread Class:
2a
First Intake Thread Direction:

Right-hand

NSN 4330-01-391-8316

Fluid Filter - Page 2 of 2

Fiig: A24000



Filtering System For Which Designed:
Full flow
Special Features:
Differential pressure electrical indicator is hirschmann connector without lamps; differential pressure setting is 73psi
Material:
Rubber synthetic seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No