## NSN 4330-01-395-0456

Fluid Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4330-01-395-0456 |
|---|
| Mounting Type:  |
| Inlet connection line and outlet connection line              |
| Body Length:  |
| 1.047 inches  |
| Body Outside Diameter:  |
| 0.438 inches  |
| Filtration Rating In Microns:                                 |
| 45.0 absolute and 17.0  |
| Differential Pressure:  |
| 500.0 pounds per square inch                                  |
| Design Type:  |
| Reusable  |
| Tempurature Rating:   |
| Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit |
| Filtering Element Quantity:                                   |
| 1   |
| Maximum Operating Pressure:                                   |
| 3000.0 pounds per square inch                                 |
| Filtering Media Design:                                       |
| Woven single filtering media response                         |
| First Intake Connection Type:                                 |
| Threaded internal tube end                                    |
| First Discharge Connection Relationship To Intake Connection: |
| Not identical   |
| First Discharge Connection Type:                              |
| Threaded internal pipe end                                    |
| First Intake Thread Series Designator:                        |
| Unjf  |
| First Discharge Thread Series Designator:                     |
| Anpt  |
| First Intake Thread Size:                                     |
| 0.375 inches  |
| First Discharge Thread Size:                                  |
| 0.125 inches  |
| First Intake Thread Class:                                    |
| 3a  |
| First Intake Thread Direction:                                |
| Right-hand  |
| First Discharge Thread Direction:                             |
| Right-hand  |

Full flow

Filtering System For Which Designed:

## NSN 4330-01-395-0456

Fluid Filter - Page 2 of 2

Material:

A24000



| Stainless steel body   |
|--|
| Media For Which Designed:  |
| Any acceptable   |
| Surface Treatment:   |
| Passivate body   |
| Surface Treatment Specification:                                   |
| Aisi 300 series, cres assn standard single treatment response body |
| Style Designator:  |
| Inline (hydraulic)   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |