

View Online at <https://aerobasegroup.com/nsn/4330-01-398-4585>

Mounting Type:

Unthreaded hole head side

Mounting Hole Quantity:

2

Drop Pressure:

20.0 pounds per square inch

Differential Pressure:

150.0 pounds per square inch

End Application:

Ticonderoga class cg (47)

Design Type:

Reusable

Tempurature Rating:

925.0 degrees fahrenheit

Features Provided:

Differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

125.0 pounds per square inch

Filtering Media Design:

Mesh single filtering media response or woven single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Threaded internal tube head side

First Intake Thread Series Designator:

Unf

First Discharge Thread Series Designator:

Unjf

First Intake Thread Size:

0.562 inches

First Discharge Thread Size:

0.5625 inches

First Intake Thread Class:

2b

First Discharge Thread Class:

3b

First Intake Thread Direction:

Right-hand

First Discharge Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Used on 4820-01-325-1400 and 4820-01-325-5371 butterfly valve

Material:

Stainless steel filtering medium

Media For Which Designed:

Air

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000