

View Online at <https://aerobasegroup.com/nsn/4330-01-399-2750>

**Current Type:**

Ac

**Filtering Material:**

Any acceptable

**Filtering Material Design:**

Spiral wound

**Filtration Rating In Microns:**

2.0

**Frequency In Hertz:**

60.0

**Drain Plug:**

Not included

**Installation Design:**

Portable

**Voltage Rating:**

Between 115.0 volts and 230.0 volts

**Bypass Valve Operation Method:**

Manual

**Horsepower Rating:**

1.000

**Unit Type:**

Multiple

**Power Source:**

Electric motor

**Rated Speed In Rpm:**

1725.0

**Maximum Operating Pressure:**

80.0 pounds per square inch

**Magnet:**

Included

**Drain Cock:**

Included

**Switch-over Valve:**

Included

**Filtering Element Quantity:**

3

**Element Reusability Feature:**

Nonreusable

**Cleaning Blade:**

Not included

**Flow Type:**

Bypass

**Bypass Valve:**

Included

**Air-bleed Valve:**

Not included

**Circulating Pump Manufacturer Name:**

Viking pump co.

**Circulating Pump Manufacturer Identifying Name:**

Rotary pump

**Circulating Pump Manufacturer Identifying Number:**

Model no. Sg0519

**Phase:**

Single/three

**Special Features:**

Two black powder baked f-1000 element housings; one powder baked b-1000 filter bag housing; 8 gpm pump with internal relief valve; glycerin filled 0-100 psi gauge

**Quantity:**

3

**Supplementary Features:**

Can be furnished with briggs & straton gasoline engine

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T384-a