## NSN 4330-01-399-2833

Pressure Fluid Filter Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-399-2833 **Current Type:** Ac Filtering Material: Any acceptable **Filtering Material Design:** Spiral wound **Filtration Rating In Microns:** 2.0 Frequency In Hertz: 60.0 **Drain Plug:** Not included Installation Design: Portable **Voltage Rating:** Between 115.0 volts and 230.0 volts **Bypass Valve Operation Method:** Manual Horsepower Rating: 0.500 **Unit Type:** Multiple **Power Source:** Electric motor Rated Speed In Rpm: 1725.0 **Maximum Operating Pressure:** 80.0 pounds per square inch Magnet: Not included **Drain Cock:** Included **Switch-over Valve:** Included **Filtering Element Quantity: Element Reusability Feature:** Nonreusable Cleaning Blade: Not included Flow Type:

**Bypass** 

## **NSN 4330-01-399-2833**Pressure Fluid Filter Unit - Page 2 of 2



Bypass Valve:
Included
Air-bleed Valve:
Not included
Circulating Pump Manufacturer Name:
Viking pump c0.
Circulating Pump Manufacturer Identifying Name:
Rotary pump
Circulating Pump Manufacturer Identifying Number:
Model no. Sg0514
Phase:
Single/three
Special Features:
One black poweder baked f-1000 element housing; onepoweder baked b-1000 filter bag housing; 5 gpm pump with internal relief valve
glycerinj filled 0-100 psi gauge
Quantity:
3
Supplementary Features:
Can be furnished with briggs & straton gasoline engine
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T384-a