
NSN 4330-01-406-8835

Fluid Filter - Page 1 of 2



Mounting Type:

Threaded hole top

Mounting Hole Quantity:

4

Body Outside Diameter:

5.300 inches

Body Height:

15.510 inches

Filtration Rating In Microns:

3.0 absolute and 0.5

Differential Pressure:

3000.0 pounds per square inch

Distance Between Mounting Hole Centers:

Between 1.970 inches and 2.200 inches

Design Type:

Reusable

Tempurature Rating:

Between 40.0 degrees fahrenheit and 212.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

6000.0 pounds per square inch

Filtering Media Design:

Layered single filtering media response

First Intake Connection Type:

Threaded internal tube side

Mounting Facility Thread Size:

0.375 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Unf

First Intake Thread Size:

1.0625 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand



NSN 4330-01-406-8835

Fluid Filter - Page 2 of 2



Filtering System For Which Designed:

Full flow

Special Features:

73 psid differential pressure setting

Material:

Steel container/cartridge

Media For Which Designed:

Any acceptable

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000