NSN 4330-01-414-7880

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-414-7880

Manustina Tuna.
Mounting Type:
Unthreaded hole top
Mounting Hole Quantity:
Body Outside Diameter:
2.810 inches
Body Height:
6.270 inches
Filtration Rating In Microns:
40.0
End Application:
4920-01-382-3479 fuel system pressure test kit; weapon system code ed, support equipment, c-17a aircraft
Design Type:
Reusable
Tempurature Rating:
Between 32.0 degrees fahrenheit and 175.0 degrees fahrenheit
Features Provided:
Drain cock
Filtering Element Quantity:
1
Maximum Operating Pressure:
250.0 pounds per square inch
First Intake Connection Type:
Threaded internal pipe head side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Intake Thread Size:
0.250 inches
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Automatic drain; bowl capaci type 4.4oz; sump capaci type 1.75oz
Material:
Zinc sediment bowl
Media For Which Designed:
Air
Style Designator:

otyle besignator.

High pressure threaded body

NSN 4330-01-414-7880

Fluid Filter - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000