# NSN 4330-01-418-7065

Fluid Filter Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-418-7065

## Mounting Type:

Bracket w/drilled hole back

### Mounting Hole Diameter:

0.375 inches

## Mounting Hole Quantity:

8

### **Filtration Rating In Microns:**

10.0

#### **Drop Pressure:**

2.5 pounds per square inch

#### **Distance Between Mounting Hole Centers:**

Between 5.940 inches and 12.750 inches

#### Design Type:

Reusable

#### **Tempurature Rating:**

Between -40.0 degrees fahrenheit and 255.0 degrees fahrenheit

## Unit Quantity:

3

#### Features Provided:

Drain plug

## **Bracket Quantity:**

1

## Filtering Element Quantity:

3

# Maximum Operating Pressure:

15.0 pounds per square inch

# First Intake Connection Type:

Threaded external pipe side

# First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

# First Intake Thread Series Designator:

Npt

## First Intake Thread Size:

0.750 inches

# First Intake Thread Direction:

Right-hand

# Filtering System For Which Designed:

Full flow

# **Special Features:**

Max flow rate is 540 gph; 22in. H, 21.5in. W, 11.8in. Dp  $% \left( {{\left( {{{\rm{A}}} \right)}_{{\rm{A}}}} \right)$ 

# Media For Which Designed:

Fuel/oil, hydrocarbon and gas

# NSN 4330-01-418-7065

Fluid Filter Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A24000

