NSN 4330-01-423-1925

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-423-1925

Mounting Type:
Unthreaded hole base
Mounting Hole Diameter:
1.000 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
30.000 inches
Body Height:
76.250 inches
Drop Pressure:
4.5 pounds per square inch
End Application:
Weapons system th, strategic sealift conversion ships class
Design Type:
Reusable
Tempurature Rating:
250.0 degrees fahrenheit
Features Provided:
Drain plug
Filtering Element Quantity:
1
1 Maximum Operating Pressure:
Maximum Operating Pressure:
Maximum Operating Pressure: 150.0 pounds per square inch
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches First Intake Flange Shape Style:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes Filtering System For Which Designed:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes Filtering System For Which Designed: Full flow
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes Filtering System For Which Designed: Full flow Special Features:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes Filtering System For Which Designed: Full flow Special Features: Has one clean and one dirty drain each with 0.75in. 150
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes Filtering System For Which Designed: Full flow Special Features: Has one clean and one dirty drain each with 0.75in. 150 Material:
Maximum Operating Pressure: 150.0 pounds per square inch First Intake Connection Type: Raised face flange side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection Distance From Bottom Of Body To Center Of Inlet: 27.000 inches First Intake Flange Shape Style: Round w/unthreaded bolt holes Filtering System For Which Designed: Full flow Special Features: Has one clean and one dirty drain each with 0.75in. 150 Material: Steel body

Leg mounted body and cover assembly (swing bolted)

NSN 4330-01-423-1925

Fluid Filter - Page 2 of 2



	L -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000