

View Online at <https://aerobasegroup.com/nsn/4330-01-426-7053>

Mounting Type:

Unthreaded hole top

Mounting Hole Diameter:

0.440 inches

Mounting Hole Quantity:

4

Body Outside Diameter:

7.000 inches

Body Height:

16.090 inches

Filtration Rating In Microns:

7.0

Drop Pressure:

7.0 pounds per square inch

Differential Pressure:

48.0 pounds per square inch

Distance Between Mounting Hole Centers:

4.420 inches

End Application:

Navy weapons system th, strategic sealift conversion ships class

Design Type:

Reusable

Tempurature Rating:

225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

100.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head side

Second Intake Connection Relationship To First Intake Connection:

Identical

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Threaded external pipe bottom

First Intake Thread Series Designator:

Unf

First Discharge Thread Series Designator:

Npt

First Intake Thread Size:

1.500 inches

First Discharge Thread Size:

1.500 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

First Discharge Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Tri-color gauge

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

EII type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000