

View Online at <https://aerobasegroup.com/nsn/4330-01-429-9633>

**Mounting Type:**

Inlet connection line and outlet connection line

**Differential Pressure:**

525.0 pounds per square inch

**End Application:**

Strategic sealift conversion ships class

**Design Type:**

Reusable

**Temperature Rating:**

Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Features Provided:**

By-pass valve and drain plug and differential pressure indicator

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

350.0 pounds per square inch

**Filtering Media Design:**

Porous single filtering media response

**First Intake Connection Type:**

Threaded internal tube head side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.625 inches

**First Intake Thread Class:**

2b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Removal rating beta 8-75

**Material:**

Steel sediment bowl

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

High pressure bolted shell

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000