

View Online at <https://aerobasegroup.com/nsn/4330-01-430-3870>

Mounting Type:

Inlet connection head side and outlet connection head side

Body Outside Diameter:

3.240 inches

Body Height:

7.920 inches

Drop Pressure:

5.0 pounds per square inch

Differential Pressure:

10.0 pounds per square inch

End Application:

Navy weapons systems jy, iwo jima class lph

Design Type:

Reusable

Tempurature Rating:

175.0 degrees fahrenheit

Features Provided:

Differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

250.0 pounds per square inch

Filtering Media Design:

Molded single filtering media response

First Intake Connection Type:

Threaded internal pipe head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Nptf

First Intake Thread Size:

0.500 inches

Product Name:

Coalescing filter

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Nylon sight gauge; manual push'n'pull drain with buna-n body and brass stem; bowl capaci type 8 oz.; as part of air preparation assembly d-wk-802-24 uses wall mounting kit ps755p

Material:

Rubber buna n seal

Media For Which Designed:

Air

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000