

View Online at <https://aerobasegroup.com/nsn/4330-01-435-8826>

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

0.438 inches

Mounting Hole Quantity:

4

Body Length:

6.900 inches

Body Width:

7.100 inches

Body Height:

12.760 inches

Drop Pressure:

2.0 pounds per square inch

Distance Between Mounting Hole Centers:

6.250 inches

End Application:

Propulsion systems

Design Type:

Reusable

Temperature Rating:

Between -25.0 degrees fahrenheit and 275.0 degrees fahrenheit

Features Provided:

By-pass valve

Filtering Element Quantity:

1

Maximum Operating Pressure:

200.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head side

Second Intake Connection Relationship To First Intake Connection:

Identical

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Unthreaded external hose bottom

First Discharge Outside Diameter:

1.580 inches

First Intake Thread Series Designator:

Uns

First Intake Thread Size:

1.500 inches

First Intake Thready Qty Per Inch (tpi):

24

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Reservoir mounted; v-pak element w/a cleanliness level of 18/16/14 or better

Material:

Steel sediment bowl

Media For Which Designed:

Fuel/oil, hydrocarbon and water/alcohol mixture and water

Style Designator:

High pressure bolted shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000