

View Online at <https://aerobasegroup.com/nsn/4330-01-436-1039>

Mounting Type:

Inlet connection head and outlet connection head

Body Outside Diameter:

4.000 inches

Body Height:

10.580 inches

Filtration Rating In Microns:

19.0

Drop Pressure:

25.0 pounds per square inch

End Application:

W/s code hx, dry deck shelter

Design Type:

Reusable

Tempurature Rating:

Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit

Filtering Element Quantity:

1

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal pipe head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Unc

First Intake Thread Size:

1.062 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Pleated cellulose element is reinforced by wire to prevent bunching

Material:

Cellulose filtering medium

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000