NSN 4330-01-439-5696



Fluid Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4330-01-439-5696 **Mounting Type:** Threaded hole top **Mounting Hole Quantity:** 2 **Body Outside Diameter:** 3.700 inches **Body Height:** 7.300 inches **Filtration Rating In Microns:** 25.0 **Differential Pressure:** 100.0 pounds per square inch **Distance Between Mounting Hole Centers:** 1.500 inches **End Application:** Navy weapons system code ka, usns stalwart class tagos **Design Type:** Reusable **Tempurature Rating:** Between -40.0 degrees fahrenheit and 250.00 degrees fahrenheit **Features Provided:** By-pass valve **Filtering Element Quantity: Mounting Facility Thread Series Designator:** Unc **Maximum Operating Pressure:** 250.0 pounds per square inch Filtering Media Design: Matted single filtering media response **First Intake Connection Type:** Threaded internal pipe head side **Mounting Facility Thread Size:**

0.250 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Nptf

First Intake Thread Size:

0.750 inches

First Intake Thread Direction:

Right-hand

NSN 4330-01-439-5696

Fluid Filter - Page 2 of 2

Fiig: A24000



Filtering System For Which Designed:
Full flow
Special Features:
Bypass cracking pressure, 15psid; return line gauge port drilled, tapped and plugged
Material:
Steel container/cartridge
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Threaded shell (mason jar)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No