

View Online at <https://aerobasegroup.com/nsn/4330-01-439-5696>

**Mounting Type:**

Threaded hole top

**Mounting Hole Quantity:**

2

**Body Outside Diameter:**

3.700 inches

**Body Height:**

7.300 inches

**Filtration Rating In Microns:**

25.0

**Differential Pressure:**

100.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

1.500 inches

**End Application:**

Navy weapons system code ka, usns stalwart class tagos

**Design Type:**

Reusable

**Temperature Rating:**

Between -40.0 degrees fahrenheit and 250.00 degrees fahrenheit

**Features Provided:**

By-pass valve

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Filtering Media Design:**

Matted single filtering media response

**First Intake Connection Type:**

Threaded internal pipe head side

**Mounting Facility Thread Size:**

0.250 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Nptf

**First Intake Thread Size:**

0.750 inches

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Bypass cracking pressure, 15psid; return line gauge port drilled, tapped and plugged

**Material:**

Steel container/cartridge

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

Threaded shell (mason jar)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000