## NSN 4330-01-439-6167

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-439-6167

Mounting Type:
Unthreaded hole center
Mounting Hole Diameter:
0.551 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
8.190 inches
Body Height:
16.610 inches
Filtration Rating In Microns:
10.0
Drop Pressure:
2.0 pounds per square inch
Differential Pressure:
145.0 pounds per square inch
Distance Between Mounting Hole Centers:
6.540 inches
Design Type:
Reusable
Tempurature Rating:
Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit
Features Provided:
By-pass valve and differential pressure indicator
Filtering Element Quantity:
1
Maximum Operating Pressure:
360.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Plain face flange side near top
First Discharge Connection Relationship To Intake Connection:
Not identical
First Discharge Connection Type:
Threaded internal pipe bottom
First Intake Flange Shape Style:
Hexagon w/threaded bolt holes
First Intake Flange Face Style:
Plain
Second Discharge Thread Series Designator:

Npt

## **NSN 4330-01-439-6167** Fluid Filter - Page 2 of 2



Second Discharge Thread Size:
3.000 inches
Product Name:
In-tank return line filter
Second Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Standard return line bypass valve with cracking pressure of 43 psid
Material:
Plastic polytetrafluoroethylene seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Ell type (hydraulic)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000