NSN 4330-01-440-9365

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-440-9365

Mounting Type:
Unthreaded hole center
Mounting Hole Diameter:
0.217 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
3.540 inches
Body Height:
9.600 inches
Filtration Rating In Microns:
10.0 absolute
Drop Pressure:
2.0 pounds per square inch
Differential Pressure:
250.0 pounds per square inch
Distance Between Mounting Hole Centers:
2.870 inches
End Application:
Weapons code thn, strategic sealift conversion ships class
Design Type:
Reusable
Reusable Tempurature Rating:
Tempurature Rating:
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided:
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity:
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: 1
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: 1 Maximum Operating Pressure:
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: 1 Maximum Operating Pressure: 360.0 pounds per square inch
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: 1 Maximum Operating Pressure: 360.0 pounds per square inch Filtering Media Design:
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: 1 Maximum Operating Pressure: 360.0 pounds per square inch Filtering Media Design: Pleated single filtering media response
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: Maximum Operating Pressure: 360.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type:
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: 1 Maximum Operating Pressure: 360.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal tube head side
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: Maximum Operating Pressure: 360.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal tube head side First Discharge Connection Relationship To Intake Connection:
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: Maximum Operating Pressure: 360.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal tube head side First Discharge Connection Relationship To Intake Connection: Not identical
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: Maximum Operating Pressure: 360.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal tube head side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type:
Tempurature Rating: Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit Features Provided: By-pass valve and differential pressure indicator and magnet Filtering Element Quantity: 1 Maximum Operating Pressure: 360.0 pounds per square inch Filtering Media Design: Pleated single filtering media response First Intake Connection Type: Threaded internal tube head side First Discharge Connection Relationship To Intake Connection: Not identical First Discharge Connection Type: Threaded internal tube bottom

Un

NSN 4330-01-440-9365 Fluid Filter - Page 2 of 2



First Intake Thread Size:
1.3125 inches
First Discharge Thread Size:
1.3125 inches
First Intake Thready Qty Per Inch (tpi):
12
First Discharge Thready Qty Per Inch (tpi):
12
First Intake Thread Class:
2b
First Discharge Thread Class:
2b
First Intake Thread Direction:
Right-hand
First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
n-tank return line filter; electrical clogging indicator with 29psi trip pressure; cracking pressure of bypass valve 43 psid; bypass valve is
built into the filter element
Material:
Rubber buna n seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Ell type (hydraulic)
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A24000