NSN 4330-01-442-3660

Fluid Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4330-01-442-3660 | | | | | |
|---|--|--|--|--|--|
| Mounting Type: | | | | | |
| Inlet connection head side and outlet connection head side | | | | | |
| Body Outside Diameter: | | | | | |
| 3.300 inches | | | | | |
| Body Height: | | | | | |
| 7.400 inches | | | | | |
| Filtration Rating In Microns: | | | | | |
| 5.0 | | | | | |
| Drop Pressure: | | | | | |
| 5.0 pounds per square inch | | | | | |
| End Application: | | | | | |
| 1740-01-327-6831; weapons code 40a, helicopter, black hawk uh-60a | | | | | |
| Design Type: | | | | | |
| Reusable | | | | | |
| Tempurature Rating: | | | | | |
| 275.0 degrees fahrenheit | | | | | |
| Filtering Element Quantity: | | | | | |
| 1 | | | | | |
| Maximum Operating Pressure: | | | | | |
| 200.0 pounds per square inch | | | | | |
| Filtering Media Design: | | | | | |
| Molded single filtering media response | | | | | |
| First Intake Connection Type: | | | | | |
| Threaded internal pipe head side | | | | | |
| First Discharge Connection Relationship To Intake Connection: | | | | | |
| Identical to first intake connection | | | | | |
| First Intake Thread Series Designator: | | | | | |
| Npt | | | | | |
| First Intake Thread Size: | | | | | |
| 0.500 inches | | | | | |
| Product Name: | | | | | |
| Particulate air filter | | | | | |
| First Intake Thread Direction: | | | | | |
| Right-hand | | | | | |
| Filtering System For Which Designed: | | | | | |
| Full flow | | | | | |
| Special Features: | | | | | |
| Fluorocarbon seals; automatic mechanical drain; baffles | | | | | |
| Material: | | | | | |
| Zinc alloy container/cartridge | | | | | |

Air

Media For Which Designed:

NSN 4330-01-442-3660

Fluid Filter - Page 2 of 2



| Styl | | | |
|------|--|--|--|
| | | | |

Quick-disconnect shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000