

View Online at <https://aerobasegroup.com/nsn/4330-01-442-6592>

Mounting Type:

Threaded hole top

Mounting Hole Quantity:

2

Body Outside Diameter:

3.000 inches

Body Height:

8.680 inches

Filtration Rating In Microns:

9.5 absolute

Distance Between Mounting Hole Centers:

0.750 inches

End Application:

Navy weapons code jp, supply class aoe

Design Type:

Reusable

Tempurature Rating:

225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

3000.0 pounds per square inch

First Intake Connection Type:

Threaded internal pipe head side

Mounting Facility Thread Size:

0.250 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Nptf

First Intake Thread Size:

0.750 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Bypass valve setting: cracking 40 psid, full flow 75 psid; cartridge dirt alarm type; used as pressure filter in emergency backup hydraulic power unit for elevator door

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000