

View Online at <https://aerobasegroup.com/nsn/4330-01-442-6592>

**Mounting Type:**

Threaded hole top

**Mounting Hole Quantity:**

2

**Body Outside Diameter:**

3.000 inches

**Body Height:**

8.680 inches

**Filtration Rating In Microns:**

9.5 absolute

**Distance Between Mounting Hole Centers:**

0.750 inches

**End Application:**

Navy weapons code jp, supply class aoe

**Design Type:**

Reusable

**Tempurature Rating:**

225.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**First Intake Connection Type:**

Threaded internal pipe head side

**Mounting Facility Thread Size:**

0.250 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Nptf

**First Intake Thread Size:**

0.750 inches

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Bypass valve setting: cracking 40 psid, full flow 75 psid; cartridge dirt alarm type; used as pressure filter in emergency backup hydraulic power unit for elevator door

**Material:**

Rubber buna n seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000