

View Online at <https://aerobasegroup.com/nsn/4330-01-442-6621>

**Mounting Type:**

Unthreaded hole head

**Mounting Hole Diameter:**

0.350 inches

**Mounting Hole Quantity:**

3

**Body Outside Diameter:**

5.250 inches

**Body Height:**

10.740 inches

**Filtration Rating In Microns:**

10.2 absolute

**Distance Between Mounting Hole Centers:**

5.250 inches

**End Application:**

Navy weapons code jp, supply class aoe

**Design Type:**

Reusable

**Temperature Rating:**

225.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

100.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal pipe head side

**First Discharge Connection Relationship To Intake Connection:**

Not identical

**First Intake Thread Series Designator:**

Nptf

**First Intake Thread Size:**

1.000 inches

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Bypass valve setting- cracking 25psid, full flow 39psid; tri-color gauge dirt alarm type; used as in-tank return line filter in emergency backup hydraulic power unit for elevator door

**Material:**

Steel container/cartridge

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

EII type (hydraulic)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000