NSN 4330-01-444-2570

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-444-2570

| Mounting Type: |
|---|
| Unthreaded hole head side |
| Mounting Hole Diameter: |
| 0.310 inches |
| Mounting Hole Quantity: |
| 4 |
| Body Outside Diameter: |
| 4.500 inches |
| Body Height: |
| 10.550 inches |
| Filtration Rating In Microns: |
| 10.0 |
| Distance Between Mounting Hole Centers: |
| Between 2.500 inches and 3.810 inches |
| End Application: |
| WEAP-ON-SCO-DEFN |
| Design Type: |
| Reusable |
| Features Provided: |
| Differential pressure indicator |
| Filtering Element Quantity: |
| 1 |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch |
| First Intake Connection Type: |
| Threaded internal tube head side |
| First Discharge Connection Relationship To Intake Connection: |
| Identical to first intake connection |
| First Intake Thread Series Designator: |
| Unf |
| First Intake Thread Size: |
| 1.312 inches |
| First Intake Thread Class: |
| 2b |
| First Intake Thread Direction: |
| Right-hand |
| Filtering System For Which Designed: |
| Full flow |
| Special Features: |
| Has differential pressure electrical switch and mechanical indicator set at 35psid; inlet and outlet ports are for 37deg flare fittings |
| Material: |
| Aluminum body |

NSN 4330-01-444-2570

Fluid Filter - Page 2 of 2



| Media | For | Which | Desig | ned: |
|---------|-----|----------|-------|--------|
| IVICUIA | ГОІ | VVIIICII | Desid | iiieu. |

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000