

View Online at <https://aerobasegroup.com/nsn/4330-01-444-4295>

Mounting Type:

Threaded hole top

Mounting Hole Quantity:

4

Body Outside Diameter:

5.700 inches

Body Height:

18.190 inches

Filtration Rating In Microns:

25.0

Differential Pressure:

150.0 pounds per square inch

Distance Between Mounting Hole Centers:

Between 1.410 inches and 2.760 inches

End Application:

Navy weapons code th, strategic sealift conversion ships class

Mounting Facility Thread Direction:

Right-hand

Design Type:

Reusable

Temperature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

600.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head side

Mounting Facility Thread Size:

0.500 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Unf

First Intake Thread Size:

1.500 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Bypass valve setting 50 psid; has differential pressure indicator with no thermal lockout and manual reset preset to 35 psid

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon and water/alcohol mixture

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000