

View Online at <https://aerobasegroup.com/nsn/4330-01-444-4295>

**Mounting Type:**

Threaded hole top

**Mounting Hole Quantity:**

4

**Body Outside Diameter:**

5.700 inches

**Body Height:**

18.190 inches

**Filtration Rating In Microns:**

25.0

**Differential Pressure:**

150.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

Between 1.410 inches and 2.760 inches

**End Application:**

Navy weapons code th, strategic sealift conversion ships class

**Mounting Facility Thread Direction:**

Right-hand

**Design Type:**

Reusable

**Temperature Rating:**

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

600.0 pounds per square inch

**First Intake Connection Type:**

Threaded internal tube head side

**Mounting Facility Thread Size:**

0.500 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Unf

**First Intake Thread Size:**

1.500 inches

**First Intake Thread Class:**

2b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Bypass valve setting 50 psid; has differential pressure indicator with no thermal lockout and manual reset preset to 35 psid

**Material:**

Steel container/cartridge

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water/alcohol mixture

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000