NSN 4330-01-452-1204

Fluid Filter - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/4330-01-452-1204
Mounting Type:
Threaded hole top
Mounting Hole Quantity:
4
Body Outside Diameter:
5.500 inches
Body Height:
14.610 inches
Filtration Rating In Microns:
20.0
Drop Pressure:
0.18 pounds per square inch
Differential Pressure:
100.0 pounds per square inch
Distance Between Mounting Hole Centers:
2.000 inches
End Application:
3930-01-417-2886, army weapons code 93a, truck lift, fork model 1000m
Design Type:
Reusable
Tempurature Rating:
Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unc
Maximum Operating Pressure:
150.0 pounds per square inch
First Intake Connection Type:
Threaded internal tube head side
Mounting Facility Thread Size:
0.3125 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Un
First Intake Thread Size:
1.250 inches
First Intake Thready Qty Per Inch (tpi):
20

2b

First Intake Thread Class:

NSN 4330-01-452-1204

Fluid Filter - Page 2 of 2



First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Material:
Glass fiber filtering medium
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Threaded shell (mason jar)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A24000