## NSN 4330-01-452-3294

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-452-3294
Mounting Type:
Threaded hole top
Mounting Hole Quantity:
4
Body Outside Diameter:
5.000 inches
Body Height:
7.920 inches
Distance Between Mounting Hole Centers:
Between 2.440 inches and 4.370 inches
End Application:
Navy w/s code ka, usns stalwart class tagos
Design Type:
Reusable
Tempurature Rating:
Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit
Features Provided:
By-pass valve and differential pressure indicator and drain plug
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unc
Unc Maximum Operating Pressure:
Maximum Operating Pressure:
Maximum Operating Pressure: 800.0 pounds per square inch
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type:
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size:
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size: 0.3125 inches
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size: 0.3125 inches First Discharge Connection Relationship To Intake Connection:
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size: 0.3125 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size: 0.3125 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator:
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size: 0.3125 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size: 0.3125 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size:
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size: 0.3125 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size: 1.500 inches
Maximum Operating Pressure:  800.0 pounds per square inch  First Intake Connection Type: Threaded internal pipe head side  Mounting Facility Thread Size: 0.3125 inches  First Discharge Connection Relationship To Intake Connection: Identical to first intake connection  First Intake Thread Series Designator:  Npt  First Intake Thread Size: 1.500 inches  First Intake Thread Direction:
Maximum Operating Pressure: 800.0 pounds per square inch First Intake Connection Type: Threaded internal pipe head side Mounting Facility Thread Size: 0.3125 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Intake Thread Size: 1.500 inches First Intake Thread Direction: Right-hand
Maximum Operating Pressure:  800.0 pounds per square inch  First Intake Connection Type: Threaded internal pipe head side  Mounting Facility Thread Size: 0.3125 inches  First Discharge Connection Relationship To Intake Connection: Identical to first intake connection  First Intake Thread Series Designator: Npt  First Intake Thread Size: 1.500 inches  First Intake Thread Direction: Right-hand  Filtering System For Which Designed:

**Material:**Rubber buna n seal

## NSN 4330-01-452-3294

Fluid Filter - Page 2 of 2



Media	For	Which	Design	ed:

Fuel/oil, hydrocarbon

**Style Designator:** 

Threaded shell (mason jar)

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A24000