

View Online at <https://aerobasegroup.com/nsn/4330-01-454-4664>

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

0.350 inches

Mounting Hole Quantity:

3

Body Outside Diameter:

5.250 inches

Body Height:

11.620 inches

Filtration Rating In Microns:

10.2 absolute

Drop Pressure:

4.0 pounds per square inch

Differential Pressure:

400.0 pounds per square inch

Distance Between Mounting Hole Centers:

5.250 inches

End Application:

Navy weapons code ka, usns stalwart class tagos

Design Type:

Reusable

Tempurature Rating:

225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

100.0 pounds per square inch

First Intake Connection Type:

Threaded internal pipe head side

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Threaded external pipe bottom

First Intake Thread Series Designator:

Nptf

First Discharge Thread Series Designator:

Npt

First Intake Thread Size:

1.000 inches

First Discharge Thread Size:

1.500 inches

First Intake Thread Direction:

Right-hand

First Discharge Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Bypass valve cracking set at 25psi; differential pressure indicator is heavy duty electric switch with conduit connection; 40gpm in-tank return line filter

Material:

Steel container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

E11 type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000