

View Online at <https://aerobasegroup.com/nsn/4330-01-456-4689>

Mounting Type:

Inlet connection head side and outlet connection head side

Body Outside Diameter:

98.0 millimeters

Body Height:

233.0 millimeters

Filtration Rating In Microns:

10.0

Differential Pressure:

200.0 pounds per square inch

End Application:

Weapons code kan, usns stalwart class tagos

Design Type:

Reusable

Temperature Rating:

Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

By-pass valve and differential pressure indicator

Maximum Operating Pressure:

3000.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal tube head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.062 inches

First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

2b

Product Name:

Pressure line filter

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

15 gpm flow rate; 40 psid by-pass valve setting

Media For Which Designed:

Fuel/oil, hydrocarbon and water/alcohol mixture

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000