

View Online at <https://aerobasegroup.com/nsn/4330-01-456-4689>

**Mounting Type:**

Inlet connection head side and outlet connection head side

**Body Outside Diameter:**

98.0 millimeters

**Body Height:**

233.0 millimeters

**Filtration Rating In Microns:**

10.0

**Differential Pressure:**

200.0 pounds per square inch

**End Application:**

Weapons code kan, usns stalwart class tagos

**Design Type:**

Reusable

**Temperature Rating:**

Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Features Provided:**

By-pass valve and differential pressure indicator

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal tube head side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.062 inches

**First Intake Thready Qty Per Inch (tpi):**

12

**First Intake Thread Class:**

2b

**Product Name:**

Pressure line filter

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

15 gpm flow rate; 40 psid by-pass valve setting

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water/alcohol mixture

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000