

View Online at <https://aerobasegroup.com/nsn/4330-01-461-2701>

Mounting Type:

Bracket w/drilled hole side

Mounting Hole Diameter:

0.562 inches

Mounting Hole Quantity:

4

Body Outside Diameter:

7.810 inches

Body Height:

24.380 inches

Mounting Flange Bolt Hole Quantity:

4

Filtration Rating In Microns:

3.0 absolute

Distance Between Mounting Hole Centers:

4.000 inches

End Application:

Filter, fluid; w/s usns stalwart class tagos

Design Type:

Reusable

Temperature Rating:

Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit

Features Provided:

By-pass valve and drain plug

Bracket Quantity:

1

Filtering Element Quantity:

1

Maximum Operating Pressure:

400.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Plain face flange side

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Plain face flange bottom

First Intake Flange Shape Style:

Oval w/threaded bolt holes

First Discharge Flange Shape Style:

Oval w/threaded bolt holes

First Intake Flange Face Style:

Plain

First Discharge Flange Face Style:

Plain

First Intake Flange Thickness:

0.620 inches

First Discharge Flange Thickness:

0.620 inches

First Intake Flange Length:

3.690 inches

Err Default:

Err default

First Intake Flange Width:

3.160 inches

Err Default:

Err default

Filtering System For Which Designed:

Full flow or by-pass flow

Special Features:

Split flange ports per sae j518c

Material:

Rubber buna n seal

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Anodize body

Style Designator:

EII type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000