

View Online at <https://aerobasegroup.com/nsn/4330-01-462-6716>

Current Type:

Ac

Filtering Material:

Glass fiber

Filtering Material Design:

Pleated

Filtration Rating In Microns:

3.0

Frequency In Hertz:

Between 50.0 and 60.0

Drain Plug:

Not included

Installation Design:

Portable

Voltage Rating:

110.0 pounds per hour dry and 120.0 pounds per hour with retaining chain

Horsepower Rating:

0.250

Unit Type:

Single

Power Source:

Electric motor

Maximum Operating Pressure:

50.0 pounds per square inch

Magnet:

Not included

Drain Cock:

Not included

Filtering Element Quantity:

1

Element Reusability Feature:

Nonreusable

Cleaning Blade:

Not included

Flow Type:

Full

Air-bleed Valve:

Included

Phase:

Single

Special Features:

Flow capacity maximum 4 gallons per minute; operating temp (unit) minus 15 degrees f to 180 degrees f, (wand/hose) 25 degrees f to 120 degrees f; noise level less than 70 db at 3 ft; housing material (cast aluminum), cover (die cast aluminum), handle/indicator (nylon), wands/hose (pvc), fittings (brass), seals (viton/carboxylated nitrile); estimated element life 370 gal for new oil at iso 20/16; filter element capaci type 13 grams dirt; gerotor pump with visible serviceable inlet strainer; auxiliary inlet/outlet ports; not for flammable liquids such as

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T384-a