NSN 4330-01-467-3590

Fluid Filter Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-467-3590

Mounting Type:
Bracket w/drilled hole back
Mounting Hole Diameter:
0.375 inches
Mounting Hole Quantity:
6
Filtration Rating In Microns:
10.0
Drop Pressure:
3.7 pounds per square inch
Distance Between Mounting Hole Centers:
3.880 inches
Design Type:
Reusable
Tempurature Rating:
Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit
Unit Quantity:
2
Bracket Quantity:
1
Filtering Element Quantity:
2
Maximum Operating Pressure:
15.0 pounds per square inch
First Intake Connection Type:
Threaded internal tube side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Outside Diameter:
0.8750 inches
First Intake Thread Series Designator:
Unf
First Discharge Thread Series Designator:
Unf
First Intake Thready Qty Per Inch (tpi):
14
First Discharge Thready Qty Per Inch (tpi):
14
Filtering System For Which Designed:
Full flow
Charles Factures

Max flow rate: 360 gph; filter element: 2020 series; height: 22 in.; width: 18.8 in.; depth: 11 in.; bowl water capacity: 610 ml; overhead clearance: 5 in. (required for element removal/servicing

NSN 4330-01-467-3590

Fluid Filter Assembly - Page 2 of 2



Material:

Metal body

Media For Which Designed:

Fuel/oil, hydrocarbon

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000