

View Online at <https://aerobasegroup.com/nsn/4330-01-467-3590>

Mounting Type:

Bracket w/drilled hole back

Mounting Hole Diameter:

0.375 inches

Mounting Hole Quantity:

6

Filtration Rating In Microns:

10.0

Drop Pressure:

3.7 pounds per square inch

Distance Between Mounting Hole Centers:

3.880 inches

Design Type:

Reusable

Tempurature Rating:

Between -40.0 degrees fahrenheit and 225.0 degrees fahrenheit

Unit Quantity:

2

Bracket Quantity:

1

Filtering Element Quantity:

2

Maximum Operating Pressure:

15.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Outside Diameter:

0.8750 inches

First Intake Thread Series Designator:

Unf

First Discharge Thread Series Designator:

Unf

First Intake Thready Qty Per Inch (tpi):

14

First Discharge Thready Qty Per Inch (tpi):

14

Filtering System For Which Designed:

Full flow

Special Features:

Max flow rate: 360 gph; filter element: 2020 series; height: 22 in.; width: 18.8 in.; depth: 11 in.; bowl water capacity: 610 ml; overhead clearance: 5 in. (required for element removal/servicing)

Material:

Metal body

Media For Which Designed:

Fuel/oil, hydrocarbon

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000