

View Online at <https://aerobasegroup.com/nsn/4330-01-470-6237>

Mounting Type:

Inlet connection side near top and outlet connection side near top

Body Outside Diameter:

Between 2.750 inches and 3.750 inches

Body Height:

Between 8.000 inches and 8.250 inches

Filtration Rating In Microns:

3.0 absolute

End Application:

4500 series filter with 5000 and 6000 psi; wsd: whidbey island class lsd

Design Type:

Reusable

Filtering Element Quantity:

1

Maximum Operating Pressure:

6000.0 pounds per square inch

First Intake Connection Type:

Threaded internal pipe side near top

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Intake Thread Size:

0.750 inches

First Intake Thread Qty Per Inch (tpi):

12

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

By-pass flow or full flow

Special Features:

Item includes head, fluid filter p/n 4575g-vr with bypass relief valve, filter bowl p/n 45623g, filter element p/n 535f-b3an, visual indicator p/n 45328g, electrical indicator, o-ring p/n 523118 and o-ring 521418, quantity type 1 each on 4500 series filter, for pneumatic or hydraulic systems

Material:

Steel comp 303 frame

Style Designator:

Threaded shell (mason jar)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000