

View Online at <https://aerobasegroup.com/nsn/4330-01-474-5525>

**Mounting Type:**

Threaded hole head

**Mounting Hole Quantity:**

3

**Body Outside Diameter:**

4.140 inches

**Body Height:**

7.820 inches

**Filtration Rating In Microns:**

10.0

**Distance Between Mounting Hole Centers:**

2.000 inches

**End Application:**

Hydraulic filtration various applications

**Design Type:**

Reusable

**Tempurature Rating:**

Between -4.0 degrees fahrenheit and 212.0 degrees fahrenheit

**Features Provided:**

Differential pressure indicator

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

250.0 pounds per square inch

**First Intake Connection Type:**

Threaded internal pipe top side

**Mounting Facility Thread Size:**

0.312 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Discharge Connection Type:**

Threaded internal pipe top side

**First Intake Thread Series Designator:**

Nptf

**First Discharge Thread Series Designator:**

Nptf

**First Intake Thread Size:**

0.750 inches

**First Discharge Thread Size:**

0.750 inches

**First Intake Thread Direction:**

Right-hand

**First Discharge Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Die cast aluminum head; replaceable spin on filter element; visual clogging indicator with auto reset; standard length element sz 90; no bypass; electric switch dc; flow rating 15 gpm; necessary clearance for element removal 1.50 in

**Material:**

Rubber buna n seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

Threaded shell (mason jar)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000