## NSN 4330-01-480-7791

Fluid Filter Assembly - Page 1 of 2

**Surface Treatment:** 

Anodize body



View Online at https://aerobasegroup.com/nsn/4330-01-480-7791

Mounting Type:
Inlet connection line
Filtration Rating In Microns:
40.0
Drop Pressure:
10.0 pounds per square inch
Design Type:
Reusable
Tempurature Rating:
104.0 degrees fahrenheit
Unit Quantity:
1
Filtering Element Quantity:
1
Maximum Operating Pressure:
3000.0 pounds per square inch
First Intake Connection Type:
Threaded internal tube line
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Unjf
First Intake Thread Size:
1.0625 inches
First Intake Thready Qty Per Inch (tpi):
12
First Intake Thread Class:
3a
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Filter-in-line; filter element, 304 stainless steel, pleated, microveave wire mesh, welded; o-ring buna "n"; length 7.000; diameter 2.000;
style inline hydraulic
Material:
Aluminum alloy body
Material Specification:
Dod-std-100 federal standard single material response body and qq-a-225/6 federal specification single material response body
Media For Which Designed:
Air or fuel/oil hydrocarbon

## NSN 4330-01-480-7791

Fluid Filter Assembly - Page 2 of 2



Surface Treatment S	pecification:
---------------------	---------------

Mil-a-8625, type ii, class 2 military specification single treatment response body

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A24000

Mil-std (military Standard):

Mil-a-8625 spec.