

View Online at <https://aerobasegroup.com/nsn/4330-01-481-4530>

**Mounting Type:**

Threaded hole head

**Mounting Hole Quantity:**

4

**Body Outside Diameter:**

3.580 inches

**Body Height:**

7.360 inches

**Filtration Rating In Microns:**

20.0 absolute

**Drop Pressure:**

12.0 pounds per square inch

**Differential Pressure:**

2250.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

Between 1.181 inches and 1.1772 inches

**End Application:**

Test stand hydraulic

**Mounting Facility Thread Direction:**

Right-hand

**Design Type:**

Reusable

**Tempurature Rating:**

Between 15.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Features Provided:**

Differential pressure indicator

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unf

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response or porous single filtering media response

**First Intake Connection Type:**

Threaded internal tube head side

**Mounting Facility Thread Size:**

0.250 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Intake Thread Size:**

1.062 inches

**First Intake Thready Qty Per Inch (tpi):**

12

**First Intake Thread Class:**

2b

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Pop-up type indicator; w/by-pass

**Material:**

Rubber buna n seal

**Media For Which Designed:**

Fuel/oil, hydrocarbon and water/alcohol mixture

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000