

View Online at <https://aerobasegroup.com/nsn/4330-01-483-9441>

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

0.560 inches

Mounting Hole Quantity:

3

Body Outside Diameter:

4.750 inches

Body Width:

4.000 inches

Body Height:

10.812 inches

Differential Pressure:

900.0 pounds per square inch

End Application:

Filter; w/s arleigh burke class ddg

Tempurature Rating:

250.0 degrees fahrenheit

Features Provided:

Drain plug

Filtering Element Quantity:

1

Maximum Operating Pressure:

300.0 pounds per square inch

First Intake Connection Type:

Threaded internal pipe head side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

9.375 inches

First Intake Thread Series Designator:

Unf

First Intake Thread Size:

1.0625 inches

First Intake Thread Class:

2b

First Intake Thread Direction:

Right-hand

Special Features:

Head meterial ductile iron mil-i-24137; interior finish zinc phosphate dip; exterior finish gray lacquer primer paint; approx fluid volume 3 pints; inlet, outlet and drain connections per ms-16142

Material:

Steel container/cartridge

Surface Treatment:

Paint body

Special Test Features:

Leak test 100 percent at 50 to 60 psi under water

Style Designator:

Unthreaded shell

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000