

View Online at <https://aerobasegroup.com/nsn/4330-01-486-6242>

Mounting Type:

Inlet connection top side or outlet connection top side

Body Outside Diameter:

3.940 inches

Body Height:

7.720 inches

Filtration Rating In Microns:

6.0 absolute

Drop Pressure:

12.0 pounds per square inch

Differential Pressure:

50.0 pounds per square inch

End Application:

W/s mhc class ships

Design Type:

Nonreusable

Features Provided:

By-pass valve

Filtering Element Quantity:

1

Maximum Operating Pressure:

10000.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube top side

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Un

First Discharge Thread Series Designator:

Un

First Intake Thread Size:

1.062 inches

First Discharge Thread Size:

1.062 inches

First Intake Thready Qty Per Inch (tpi):

A12

First Discharge Thready Qty Per Inch (tpi):

A12

First Intake Thread Class:

2b

First Discharge Thread Class:

2b

First Intake Thread Direction:

Right-hand

First Discharge Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

25 gpm maximum flow rate; latching resettable no electrical fittings; visual bypass indicator with manual reset feature; sae 12 ports, 1 1/16 12 thread

Material:

Steel comp 316l body

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000