

View Online at <https://aerobasegroup.com/nsn/4330-01-486-6242>

**Mounting Type:**

Inlet connection top side or outlet connection top side

**Body Outside Diameter:**

3.940 inches

**Body Height:**

7.720 inches

**Filtration Rating In Microns:**

6.0 absolute

**Drop Pressure:**

12.0 pounds per square inch

**Differential Pressure:**

50.0 pounds per square inch

**End Application:**

W/s mhc class ships

**Design Type:**

Nonreusable

**Features Provided:**

By-pass valve

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

10000.0 pounds per square inch

**First Intake Connection Type:**

Threaded internal tube top side

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Un

**First Discharge Thread Series Designator:**

Un

**First Intake Thread Size:**

1.062 inches

**First Discharge Thread Size:**

1.062 inches

**First Intake Thready Qty Per Inch (tpi):**

A12

**First Discharge Thready Qty Per Inch (tpi):**

A12

**First Intake Thread Class:**

2b

**First Discharge Thread Class:**

2b

**First Intake Thread Direction:**

Right-hand

**First Discharge Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

25 gpm maximum flow rate; latching resettable no electrical fittings; visual bypass indicator with manual reset feature; sae 12 ports, 1 1/16 12 thread

**Material:**

Steel comp 316l body

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000